



Technical Data Sheet

MASTER PLUS 150

API: SD/CD
SAE: 40 & 50

DESCRIPTION:

Master Plus 150 is a high-quality crankcase oil for diesel and gasoline engines. Master Plus 150 is formulated with selected high-quality base oils and a balanced package of potent and effective additives including detergent, rust inhibitor and an anti-wear agent for meeting the requirements of the API Service Classifications SD for gasoline engines and CD for diesel engines.

APPLICATIONS:

Master Plus 150 may be used in automotive diesel engines under moderate to severe conditions and four stroke petrol engines where API SD/CD oil is recommended. This oil is specially recommended for cabs, cars, buses, tractors and road trucks that requires this quality level. Meets and exceeds the requirements of API SD/CD.

BENEFITS:

- ✓ Provides efficient and economical lubrication over wide range of operating conditions
- ✓ Gives excellent control over engine wear and corrosion
- ✓ Prolongs engine's life
- ✓ Excellent performance against ring sticking
- ✓ Reduces piston grooves and deposits

TYPICAL DATA

Product	Master Plus 150
SAE Rating	40 & 50
API Performance	SD/CD

PHYSICAL CHARACTERISTICS

TEST	TEST METHOD	TYPICAL VALUE	
		40	50
SAE Rating		40	50
Kinematic Viscosity cSt @100 °C	ASTM D - 445	15.3	18.5
Viscosity Index	ASTM D - 2270	110	110
Flash Point COC, °C	ASTM D - 92	228	230
Sulphated Ash, % wt.	ASTM D - 874	0.65	0.65
Pour Point °C	ASTM D - 97	-9	-9

Packing: 01 Ltr – 04 Ltr – 05 Ltr – 06 Ltr – 08 Ltr – 10 Ltr – 20 Ltr – 105 Ltr – 205 Ltr