



**MASTER VICTORY
HYDRAULIC OIL**

“Helps to prolong equipment life through excellent hydraulic pump wear protection”

MASTER VICTORY (HYDRAULIC OIL)

MASTER VICTORY OIL is a premium quality hydraulic lubricant made from selected mineral base oils combined with anti-wear and rust inhibitor additives to produce highly stable premium hydraulic fluids, to improve the energy efficiency of the system in which it is used; and for excellent performance under severe operating conditions and extended drain intervals. It also helps to prolong equipment life through excellent hydraulic pump wear protection.

APPLICATIONS

- Specially recommended for all mobile and stationary hydraulic systems operating under the most severe conditions.
- Can also be used in circulation, splash and ring oil lubrication systems and compressors where recommended.

PERFORMANCE STANDARDS

Meets DIN 51524 part II, Cincinnati Machine P68, P69, P70, U.S. Steel 127,136; Denison HF-0, HF-2, Vickers I-286-S, M-2950-S

BENEFITS

- ☑ Longer hydraulic/machine component life
- ☑ Cleaner servo-motor valves
- ☑ Less sticking
- ☑ Superior oxidation and hydrolytic stability
- ☑ Multi-metal compatibility under wet and dry conditions
- ☑ Superior filterability by increasing filter life

TYPICAL DATA

PHYSICAL CHARACTERISTICS		ISO VISCOSITY GRADE / TYPICAL VALUE				
TEST	TEST MATHOD	H-22	H-32	H-46	H-68	H-100
Kinematic Viscosity	ASTM D 445					
at 40°C (cst)		22	32	46	68	100
at 100°C (cst)		4.3	5.4	6.7	8.6	11.1
Viscosity Index	ASTM 2270	100	99	98	97	96
Flash Point COC °C	ASTM D 92	204	209	218	223	238
Pour Point °C	ASTM D 97	-30	-30	-30	-24	-24

Packings 205 Ltr.