



Technical Data Sheet

MASTER PLUS 100

API: SD/CC
SAE: 40 & 50

DESCRIPTION:

Master Plus 100 is a premium-grade crankcase oil for use in diesel and gasoline engines under moderate to severe conditions. Master Plus 100 is blended from selected highly refined base oil stocks and selected additives to meet performance level of API service SD/CC.

APPLICATIONS:

Master Plus 100 is recommended for use in diesel and gasoline engines. Suitable for use in most commercial vehicles and light trucks.

BENEFITS:

- ✓ Master Plus 100 delivers excellent performance, provides more protection against engine deposits, wear, rust & corrosion
- ✓ Prolongs engine's life
- ✓ Suitable for mixed fleet operation
- ✓ High residence to oxidation
- ✓ Keeps engine clean
- ✓ Maintains TBN retention

TYPICAL DATA

Product	Master Plus 100
SAE Rating	40 & 50
API Performance	SD/CC

PHYSICAL CHARACTERISTICS

TEST	TEST METHOD	TYPICAL VALUE	
		40	50
Kinematic Viscosity cSt @100 °C	ASTM D - 445	15.6	18.5
Viscosity Index	ASTM D - 2270	95	95
Flash point COC, °C	ASTM D - 92	230	235
Sulphated Ash, % wt.	ASTM D - 874	0.5	0.5
Pour Point °C	ASTM D - 97	-6	-6

Packing: 04 Ltr – 10 Ltr – 20 Ltr – 105 Ltr – 205 Ltr